

# UniFi Dream Machine Special Edition

## UDM-SE

### Datasheet

#### Mechanical


Dimensions	442.4 x 43.7 x 285.6 mm (17.4 x 1.7 x 11.2")
Weight	4.95 kg (10.9 lb)
Enclosure material	Aluminium CNC, SGCC steel
Mount material	SGCC steel

#### Hardware

Processor	Quad-core ARM® Cortex®-A57 at 1.7 GHz
System memory	4 GB DDR4
On-board storage	16 GB eMMC Integrated 128 GB SSD
Management interface	Ethernet Bluetooth
Networking interface	(8) LAN: GbE RJ45 ports (1) WAN: GbE RJ45 port
SFP+ interface	(1) LAN: 10G SFP+ (1) WAN: 10G SFP+
PoE interface	(6) PoE (Pair A 1, 2+; 3, 6-) (2) PoE+ (Pair A 1, 2+; 3, 6-)
IDS/IPS throughput	3.5 Gbps* *Measured with iPerf3.
Power method	(1) Universal AC input, 100—240V AC, 4.4A Max., 50/60 Hz (1) USP-RPS DC input, 52V DC, 3.94A
Power supply	AC/DC, internal, 240W
Supported voltage range	100—240V AC
Max. power consumption	50W (Excluding PoE output)
Max. PoE wattage per port by PSE	PoE: 15.4W PoE+: 50—57V
ESD/EMP protection	Air: ± 15kV, contact: ± 8kV
LCM display	(1) 1.3" touchscreen
Button	Factory reset
Operating temperature	-10° to 40° C (14° to 104° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

#### LEDs

Ethernet	White: link/activity
SFP+	White: link/activity
HDD	White: disk activity Amber: disk error
RPS	Blue: ready



\*Requires UniFi Power Backup.

Email: [next@minitel.pt](mailto:next@minitel.pt)

Telemóvel: 213810900

[www.minitelfnext.com](http://www.minitelfnext.com)